

Audrey II

A5 II Series

Touch POS Terminal



FEATURES

- On-cell touch, optically bonded display
- Ultra-thin 7mm bezel
- 15.6" full HD with anti-glare
- High-performance Intel processor
- Windows 10/11 and Linux Ubuntu
- High-speed M.2 PCIe SSD with up to 512 G
- Support for Wi-Fi 6E
- USB Type-C connector

Audrey II

Specifications



	A5-2-T	A5-2-E
Size	15.6"	
Aspect Ratio	16:9	
Resolution	1920 x 1080	
Brightness	400 nits	
Touch	oTP (On-cell Touch Panel), Slim-Edge 7mm Bezel Design (with Anti-Glare)	
CPU	Tiger Lake UP3 Intel® Core™ i3-1115G4 Intel® Core™ i5-1145G7, vPro Intel® Core™ i7-1185G7, vPro	Elkhart Lake Intel® Celeron® J6412
Memory	DDR4 4GB, 8GB, 16GB, 32GB	DDR4 4GB, 8GB, 16GB
Storage	m.2 PCIe SSD: 128GB / 256GB / 512GB	
I/O Interface	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2) 1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 4 x USB 3.2 + 2 x USB 2.0 1 x DC + 12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer+ display)	
2nd I/O option	1. powered USB (1 x 24V + 1 x 12V) / 2. 2 x RS232 (RJ45), 0/5/12V selected in BIOS (COM3, COM4)	
Speaker	1 x speaker (3W)	
Peripheral Options	MSR, fingerprint reader, RFID/NFC, i-Button, VFD, USB 2nd display, HDMI 2nd display, 2D bar code scanner, camera, IO extension box (EX-100, EX-101, EX-300), PS-103 printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II)	
Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2	
Display Support	3 independent displays (Main Display + HDMI + Type-C)	2 independent displays (Main Display + HDMI)
Spill & Dust Resistant	Front panel IP65, whole unit IP54 certified	
Operating System	1. Windows 11 IoT Enterprise (64bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04	
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W / DC-Out 12V, 180W (for powered USB 2nd I/O)	
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (WxHxD)	364 x 288 x 201 mm / 14.33 x 11.34 x 7.91 in	
Weight	5.4 kg / 11.9 lb	

*Specification is subject to change without prior notice

Contact Now

Europe +49 40 450 635-0
 United Kingdom +44 1928 579 707
 Spain +34 913 120632
 Sloga +386 1 566 25 20
 Polen +48 22 115 93 82

info@partner-tech.eu
 sales-uk@partner-tech.eu
 comercial@partner-tech.eu
 prodaja@partner-tech.eu
 officepoland@partner-tech.eu